

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: UM00004

Issue date: 12/6/2023 Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Trade name : CPE+
(Transparent, Black, White)

1.2. Recommended use and restrictions on use

Use of the substance/mixture : 3D-Printer filament
Restrictions on use : This product must not be used in applications other than those identified above, without first seeking advice of the supplier

1.3. Supplier

UltiMaker
Watermolenweg 2
Geldermalsen, 4191 PN - The Netherlands
T +31 (0) 88 383 4000 (9 AM - 5 PM CET)
Product-Compliance@Ultimaker.com

1.4. Emergency telephone number

Emergency number : +31 (0) 88 383 4000
(during office hours: 9 AM - 5 PM CET)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Not classified

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Risk of thermal burns on contact with molten product.

2.4. Unknown acute toxicity (GHS US)

Not applicable

CPE+

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Copolyester
(proprietary ingredient)

| Name | Product identifier | Conc. (% w/w) |
|---|---------------------|---------------|
| Carbon black (Additive for CPE+ Black) | CAS-No.: 1333-86-4 | < 4 |
| Titanium dioxide (Additive for CPE+ White) | CAS-No.: 13463-67-7 | < 1 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In molten state: Hazardous vapors may be released.
First-aid measures after eye contact : Rinse eyes with water as a precaution. In the event of contact with molten product: Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : No acute and delayed symptoms and effects are observed.
Symptoms/effects after skin contact : Risk of thermal burns on contact with molten product.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Explosion hazard : Material can accumulate some static charge during transfer. Prevent build-up of electrostatic charges (e.g, by grounding).

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous decomposition products in case of fire : Under fire conditions, hazardous fumes will be present: Carbon dioxide, Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Refer to section 8.2. Remove contaminated clothing and shoes.

Emergency procedures : None in particular. In molten state: Do not breathe vapors. Ventilate spillage area. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up and put in a closed container for disposal. If melted: allow liquid to solidify before taking it up.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. In molten state: Do not breathe vapors. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials : Strong oxidizing agents.

Storage temperature : -4 – 86 °F (Relative air humidity: <50%)

Heat-ignition : Keep away from heat, sparks and flames. Keep out of direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|--|---|
| CPE+ (Transparent, Black, White) | |
| No additional information available | |
| Titanium dioxide (Additive for CPE+ White) (13463-67-7) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Titanium dioxide |
| ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| Remark (ACGIH) | TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| Regulatory reference | ACGIH 2020 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Titanium dioxide (Total dust) |
| OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| USA - IDLH - Occupational Exposure Limits | |
| US IDLH (mg/m ³) | 5000 mg/m ³ |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) (mg/m ³) | 2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale) |
| Carbon black (Additive for CPE+ Black) (1333-86-4) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Carbon black |
| ACGIH TWA (mg/m ³) | 3 mg/m ³ (I - Inhalable particulate matter) |
| Remark (ACGIH) | TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans) |
| Regulatory reference | ACGIH 2023 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Carbon black |
| OSHA PEL (TWA) (mg/m ³) | 3.5 mg/m ³ |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Ventilation conditions (1 printer): Provide a good standard of general ventilation, not less than 2 air changes per hour (assumes a room volume of: 30 m³).

8.3. Individual protection measures/Personal protective equipment

| Hand protection: | | | | |
|--|----------------------------------|-------------------|----------------|-------------|
| None under normal conditions. Use insulated gloves when handling this material hot | | | | |
| Type | Material | Permeation | Thickness (mm) | Penetration |
| In molten state: Chemically resistant protective gloves, Heat-resistant | Nitrile rubber (NBR) | 6 (> 480 minutes) | >0.35 | |
| Eye protection: | | | | |
| None under normal use. In molten state: Wear eye protection | | | | |
| Type | Use | Characteristics | | |
| Safety glasses with side shields | In molten state | | | |
| Skin and body protection: | | | | |
| None under normal use. In molten state: Wear suitable protective clothing | | | | |
| Type | Long sleeved protective clothing | | | |
| Respiratory protection: | | | | |
| None under normal use. In molten state: In case of insufficient ventilation, wear suitable respiratory equipment | | | | |
| Device | Filter type | Condition | | |
| Air-Purifying Respirator (APR), disposable | Type B/P2 | | | |

Thermal hazard protection:

Risk of thermal burns on contact with molten product. Hazardous vapors may be released. In molten state: Use respiratory protection/heat resistant gloves.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Wash hands immediately after handling the product. Take off contaminated clothing and wash before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------|
| Physical state | : Solid |
| Appearance | : Filament. |
| Color | : Various colours |
| Odor | : Slight |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : > 212 °F |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Non flammable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20°C | : No data available |
| Particle size distribution | : Not applicable |
| Relative density | : No data available |
| Density | : 1.18 g/cm ³ |
| Solubility | : Water: Negligible |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : Not applicable |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Printing process: Avoid temperature above 536 °F.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Under fire conditions, hazardous fumes will be present: Carbon dioxide, Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------------|---|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : The filament product itself (mixture) is not carcinogenic |

| Titanium dioxide (Additive for CPE+ White) (13463-67-7) | |
|--|---|
| IARC group | 2B - Possibly carcinogenic to humans, only for airborne, unbound particles of respirable size |
| In OSHA Hazard Communication Carcinogen list | Yes |

| Carbon black (Additive for CPE+ Black) (1333-86-4) | |
|---|---|
| IARC group | 2B - Possibly carcinogenic to humans, only for airborne, unbound particles of respirable size |

| | |
|-------------------------------------|---|
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : No data available |
| Symptoms/effects | : No acute and delayed symptoms and effects are observed. |
| Symptoms/effects after skin contact | : Risk of thermal burns on contact with molten product. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|--|
| Ecology - general | : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. |
|-------------------|--|

CPE+

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|-------------|
| Titanium dioxide (Additive for CPE+ White) (13463-67-7) | |
| LC50 fish 1 | > 1000 mg/l |

12.2. Persistence and degradability

| | |
|---|--------------------------------------|
| CPE+ (Transparent, Black, White) | |
| Persistence and degradability | No additional information available. |

12.3. Bioaccumulative potential

| | |
|---|--------------------------------------|
| CPE+ (Transparent, Black, White) | |
| Bioaccumulative potential | No additional information available. |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with relevant local regulations.
Product/Packaging disposal recommendations : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

| DOT | TDG | IMDG | IATA |
|---|----------------|----------------|----------------|
| 14.1. UN number | | | |
| Not regulated for transport | | | |
| 14.2. Proper Shipping Name | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| 14.3. Transport hazard class(es) | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| 14.4. Packing group | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |

CPE+

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| DOT | TDG | IMDG | IATA |
|--|----------------|----------------|----------------|
| 14.5. Environmental hazards | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| No supplementary information available | | | |

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Titanium dioxide (Additive for CPE+ White) (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

Carbon black (Additive for CPE+ Black) (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

| CPE+ (Transparent, Black, White) | |
|--|---|
| U.S. - California - Proposition 65 - Other information | <p>For product containing Carbon Black: California Proposition 65 lists Carbon Black (airborne, unbound particles of respirable size) as a substance known to the State of California to cause cancer. Some UltiMaker filaments contain low concentrations of Carbon Black, which is homogeneously bound in the polymer matrix. Given the Carbon Black is bound and concentrations are low, the risk of exposure to 'airborne, unbound particles of respirable size' during printing is considered negligible. In case 3D-prints undergo post-processing that causes dust formation, UltiMaker recommends to re-assess whether those activities may lead to significant exposure under those particular conditions and apply appropriate measures when necessary. Appropriate measures in such cases may include additional ventilation, air extraction or (face) masks, depending on the level of potential exposure.</p> <p>For products containing Titanium Dioxide: California Proposition 65 lists Titanium Dioxide (airborne, unbound particles of respirable size) as a substance known to the state California to cause cancer. Some Ultimaker filaments contain low concentrations of Titanium Dioxide, which is homogeneously bound in the polymer matrix. Given the Titanium Dioxide is bound and concentrations are low, the risk of exposure to 'airborne, unbound particles of respirable size' during printing is considered negligible. In case 3D-prints undergo post-processing that causes dust formation, UltiMaker recommends to re-assess whether those activities may lead to significant exposure under those particular conditions and apply appropriate measures when necessary. Appropriate measures in such cases may include additional ventilation, air extraction or (face) masks, depending on the level of potential exposure.</p> |

| Titanium dioxide (Additive for CPE+ White) (13463-67-7) | | | | | |
|--|---|---|---|----------------------------------|-------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| Yes | No | No | No | | |

| Carbon black (Additive for CPE+ Black) (1333-86-4) | | | | | |
|---|---|---|---|----------------------------------|-------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| Yes | No | No | No | | |

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Training advice : Ensure staff are informed of and trained on the nature of exposure and basic actions to minimise exposure.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Abbreviations and acronyms | |
|-----------------------------------|---|
| CAS-No. | Chemical Abstract Service number |
| CAS | Chemical Abstract Service number |
| DOT | Department of Transport |
| ED | Endocrine disrupting properties |
| EN | European Standard |
| GHS | Globally Harmonized System of Classification and Labelling of Chemicals |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| TDG | Transportation of Dangerous Goods |

| Indication of changes: |
|-------------------------------|
| Not applicable. |

SDS US (GHS HazCom 2012) - RHDHV

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.