

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 1 of 11

Rigid 4000 Resin

# **SECTION 1: Identification**

#### Product identifier

Product name: Rigid 4000 Resin Product code: FLRGWH01

### Recommended use of the product and restriction on use

**Relevant identified uses:** For use in Formlabs SLA Printers **Uses advised against:** Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

#### Manufacturer or supplier details

#### Manufacturer:

#### **United States**

Formlabs, Inc 35 Medford St Suite 201 Somerville, MA 02143 +1 617 855 0762

sds@formlabs.com

# **Emergency telephone number:**

### **United States**

CHEMTREC

1-800-424-9300 (24/7)

# SECTION 2: Hazard(s) identification

# GHS classification:

Skin irritation, category 2

Eye irritation, category 2A

Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Chronic aquatic hazard, category 2

#### Label elements

# Hazard pictograms:





# Signal word: Warning

### Hazard statements:

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

H411 Toxic to aquatic life with long lasting effects

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 2 of 11

#### Rigid 4000 Resin

#### Precautionary statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P271 Use only outdoors or in a well-ventilated area

P273 Avoid release to the environment

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P391 Collect spillage

P405 Store locked up

P501 Dispose of contents/container in accordance with local/regional/national regulations

#### Hazards not otherwise classified: None

# SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: Trade Secret	Methacrylate Monomer(s)	10-20
CAS number: Trade Secret	Methacrylate Monomer(s)	10-20
CAS number: Trade Secret	Urethane Dimethacrylate	35-55
CAS number: Trade Secret	Photoinitiator	<0.9

Additional Information: None

#### SECTION 4: First aid measures

# Description of first aid measures

### General notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory symptoms develop or persist, seek medical advice/attention.

# After skin contact:

Wash affected area with plenty of soap and water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, seek medical advice/attention.

# After eye contact:

Immediately rinse eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If eye irritation develops or

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 3 of 11

### Rigid 4000 Resin

persists, seek medical advice/attention.

### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

# Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing. Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

#### Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

# Immediate medical attention and special treatment

#### Specific treatment:

If respiratory symptoms persist, seek medical attention.

#### Notes for the doctor:

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### Extinguishing media

# Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable extinguishing media:

Do not use water jet.

# Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

# Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

### Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

#### SECTION 6: Accidental release measures

# Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

#### **Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

# Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 4 of 11

### Rigid 4000 Resin

clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

### SECTION 7: Handling and storage

#### Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

#### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

# SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

No occupational exposure limits noted for the ingredient(s).

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

# Information on monitoring procedures:

Not determined or not applicable.

#### Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

# Personal protection equipment

# Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

#### Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

## General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 5 of 11

Rigid 4000 Resin

before reuse. Perform routine housekeeping.

# SECTION 9: Physical and chemical properties

# Information on basic physical and chemical properties

Appearance	Grey Liquid
Odor	Characteristic acrylate
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	> 100°C
Flash point (closed cup)	> 93.5°C
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not Flammable
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	1.26 g/cm3
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	2590 cps @ 25°C
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

#### Other information

# SECTION 10: Stability and reactivity

# Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical stability:

Stable under recommended handling and storage conditions.

# Possibility of hazardous reactions:

Stable under recommended handling and storage conditions.

# Conditions to avoid:

Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

#### Incompatible materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

#### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 6 of 11 Initial preparation date: 10.19.2020

Rigid 4000 Resin

# SECTION 11: Toxicological information

### Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Methacrylate Monomer(s)	oral	LD50 Rat: >2000 mg/kg
		LD50 Rat: > 2000 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
		LD50 Rat: > 2000 mg/kg
Photoinitiator	oral	LD50 Rat: >5000 mg/kg
Urethane Dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg

### Skin corrosion/irritation

#### Assessment:

Causes skin irritation.

# Product data:

No data available.

#### Substance data:

Name	Result
Methacrylate Monomer(s)	Causes skin irritation.

# Serious eye damage/irritation

#### Assessment:

Causes serious eye irritation.

# Product data:

No data available.

# Substance data:

Name	Result
Methacrylate Monomer(s)	Causes serious eye irritation.
	Causes serious eye irritation.

# Respiratory or skin sensitization

#### Assessment:

May cause an allergic skin reaction.

#### Product data:

No data available.

# Substance data:

Name	Result
Methacrylate Monomer(s)	May cause an allergic skin reaction.
Urethane Dimethacrylate	May cause an allergic skin reaction.
Photoinitiator	May cause an allergic skin reaction.

# Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 7 of 11

Rigid 4000 Resin

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Methacrylate Monomer(s)	Not Applicable
Urethane Dimethacrylate	Not Applicable

# National Toxicology Program (NTP):

Name	Classification
Methacrylate Monomer(s)	Not Applicable
Urethane Dimethacrylate	Not Applicable

**OSHA Carcinogens:** Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation.

Product data: No data available. Substance data:

Name	Result
Methacrylate Monomer(s)	May cause respiratory irritation.

# Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 8 of 11

Rigid 4000 Resin

# SECTION 12: Ecological information

### Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	LC50 Danio rerio: 10.1 mg/L (96 h)
	EC50 Daphnia magna: 1.2 mg/L (48 h)

# Chronic (long-term) toxicity

#### Assessment:

Toxic to aquatic life with long lasting effects.

Product data: No data available.

#### Substance data:

Name	Result
Urethane Dimethacrylate	NOEC Desmodesmus subspicatus: 0.2 mg/L (72 h)

# Persistence and degradability

Product data: No data available.

#### Substance data:

Name	Result
Methacrylate Monomer(s)	Readily biodegradable (94% in 28 days).
Urethane Dimethacrylate	The substance is not readily biodegradable (22% degradation in 28 days).
Photoinitiator	The substance is not readily biodegradable.

# Bioaccumulative potential

Product data: No data available.

### Substance data:

Name	Result	
Methacrylate Monomer(s)	Low potential to bioaccumulate (BCF: 3.2; Log kow: 1.21)	
Photoinitiator	This substance is not expected to bioaccumulate because of log Kow (2.91).	
Urethane Dimethacrylate	The substance has moderate potential to adsorb to organic soil and sediment particles (Log Koc: 3.66).	

# Mobility in soil

Product data: No data available.

# Substance data:

Name	Result
Methacrylate Monomer(s)	This substance moderate potential to be adsorbed by the soil.
Photoinitiator	This substance is expected to be adsorbed by the soil.

#### Results of PBT and vPvB assessment

#### Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

#### Substance data:

# PBT assessment:

. D. assessinent	
Methacrylate Monomer(s)	This substance is not PBT.
Methacrylate Monomer(s)	This substance is not PBT.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 9 of 11

# Rigid 4000 Resin

Urethane Dimethacrylate	The substance is not PBT.	
Photoinitiator	This substance is not PBT.	
vPvB assessment:		
Methacrylate Monomer(s)	This substance is not vPvB.	
Methacrylate Monomer(s)	This substance is not vPvB.	
Urethane Dimethacrylate	The substance is not vPvB.	
Photoinitiator	This substance is not vPvB.	

Other adverse effects: No data available.

# **SECTION 13: Disposal considerations**

# Disposal methods:

As supplied, this material is not considered a hazardous waste under RCRA. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

### Contaminated packages:

Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

# **SECTION 14: Transport information**

# United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN 3082	
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer	
UN transport hazard class(es)	9	
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	None	
Additional Information	DOT: 49 CFR 171.4(c)(2) Not regulated as dangerous goods when transported in single or inner packaging of 5 L or less for liquids or net mass of 5 Kg or less for solids provided the packaging meets the requirements of 49 CFR 173.24(a)	

# International Maritime Dangerous Goods (IMDG)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 10 of 11

# Rigid 4000 Resin

Additional Information	This product is not regulated as a dangerous good when	
	transported in sizes of ≤5L or ≤5 kg provided the packaging	
	meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to	
	4.1.1.8.	

# International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated	
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer	
UN transport hazard class(es)	9	
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of ≤5L or 5≤ kg provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.	

# SECTION 15: Regulatory information

### **United States regulations**

**Inventory listing (TSCA):** All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals: None of the ingredients are listed.

**CERCLA:** None of the ingredients are listed. **RCRA:** None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

### Massachusetts Right to Know:

-	•	
Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Not Listed

# New Jersey Right to Know:

Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Not Listed

#### New York Right to Know:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.19.2020 Page 11 of 11

# Rigid 4000 Resin

Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Listed

# Pennsylvania Right to Know:

Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Not Listed

California Proposition 65: None of the ingredients are listed.

# SECTION 16: Other information

# Abbreviations and Acronyms: None

# Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 10.19.2020

**End of Safety Data Sheet**